

Valve Products



Ball Valves

- Multi-port
- Direct Mount
- Sanitary

Valve Automation

1-PIECE BALL VALVES



101R / 102R
1-Piece Ball Valve
 Reduced Port
 SS316
 Threaded
 Size: 1/4" to 2"
 Pressure: 800 PSI CWP (101R)
 2000 PSI CWP (102R)
 Temp: -20°F to 450°F
 Options: Locking Device
 Reverse Handle
 Mounting Pad (102R)



103R / 104R
1-Piece Ball Valve
 Reduced Port
 CS / SS316
 Threaded
 NPT x FNPT (104R)
 Size: 1/4" to 2" (103R)
 1/4" to 1/2" (104R)
 Pressure: 1500 to 2000 PSI CWP (103R)
 800 PSI CWP (104R)
 Temp: -20°F to 450°F


2-PIECE BALL VALVES



201F / 202F
2-Piece Ball Valve
 Full Port
 SS316 / WCB x SS316
 Threaded
 Locking Device
 Size: 1/4" to 4"
 Pressure: 2000 PSI CWP (201F)
 1000 PSI CWP (202F)
 Temp: -20°F to 450°F
 Option: Mounting Pad



201S
2-Piece Ball Valve
 Standard Port
 SS316
 Threaded
 Locking Device
 Size: 1/4" to 2"
 Pressure: 1500 to 2000 PSI CWP
 Temp: -20°F to 450°F
 Option: Mounting Pad



204F
2-Piece Ball Valve
 Full Port
 SS316
 Threaded
 ISO 5211 Direct Mount Pad
 Locking Device
 Size: 1/4" to 4"
 Pressure: 800 to 1000 PSI CWP
 Temp: -20°F to 425°F



209F
2-Piece Flanged Ball Valve
 Full Port
 SS304 / SS316 / WCB x SS316
 Flanged
 Mounting Pad
 Locking Device
 Size: 1/2" to 12"
 Pressure: ANSI 150 / 300
 Temp: -20°F to 450°F

3-PIECE BALL VALVES



302F
3-Piece Ball Valve
 Full Port
 SS316 / WCB x SS316
 Threaded, Butt / Socket Weld,
 Flanged and Grooved
 Locking Device
 Size: 1/4" to 4"
 Pressure: 800 to 1000 PSI CWP
 Temp: -20°F to 450°F



303F
3-Piece Ball Valve
 Full Port
 SS316
 Threaded, Butt / Socket Weld
 Mounting Pad
 Size: 1/4" to 2"
 Pressure: 1440 PSI CWP
 Temp: -20°F to 450°F
 Option: Locking Device



304F
3-Piece Ball Valve
 Full Port
 SS316 / WCB x SS316
 Threaded
 ISO 5211 Direct Mount Pad
 Locking Device
 Size: 1/4" to 4"
 Pressure: 800 to 1000 PSI CWP
 Temp: -20°F to 425°F



307F / 317F
3-Piece Sanitary Ball Valve
 Tube Full Port
 SS316 / SS316L
 Clamp, Tube Butt Weld and
 Extended Tube Butt Weld
 Locking Device
 Size: 1/4" to 4"
 Pressure: 600 to 1000 PSI CWP
 Temp: -20°F to 350°F (PTFE)
 Options: Tru-Drain CIP System
 Cavity Fill Seats



334S
3-Piece Ball Valve
 Standard Port
 SS316
 Threaded, Butt / Socket Weld
 ISO 5211 Direct Mount Pad
 Locking Device
 Size: 1/4" to 2"
 Pressure: 1440 PSI CWP
 Temp: -20°F to 425°F



337F
3-Piece Sanitary Ball Valve
 Tube Full Port
 SS316L
 Clamp, Tube Butt Weld and
 Extended Tube Butt Weld
 ISO 5211 Direct Mount Pad
 Locking Device
 Size: 1/4" to 4"
 Pressure: 600 to 1000 PSI CWP
 Temp: -20°F to 350°F (PTFE)
 Options: Tru-Drain CIP System
 Cavity Fill Seats

MULTI-PORT BALL VALVES



502S
Diverter Ball Valve
 Standard Port
 SS316
 Threaded
 Mounting Pad
 Locking Device
 Size: 1/4" to 2"
 Pressure: 800 to 1000 PSI CWP
 Temp: -20°F to 450°F
 Option: Bottom Entry



503F / 503S
3-Way Ball Valve
 Full or Standard Port
 SS316
 Threaded
 Mounting Pad
 Size: 1/4" to 2"
 Pressure: 800 to 1000 PSI CWP
 Temp: -20°F to 450°F
 Option: Locking Device



514F
3-Way Ball Valve
 Full or Standard Port
 SS316
 Threaded
 ISO 5211 Direct Mount Pad
 Locking Device
 Size: 1/4" to 2"
 Pressure: 800 to 1000 PSI CWP
 Temp: -20°F to 425°F



505F
3/4/5-Way Ball Valve
 Full Port
 SS316
 Threaded, Butt / Socket Weld
 Mounting Pad
 Size: 1/4" to 4"
 Pressure: 1000 PSI CWP
 Temp: -20°F to 450°F
 Option: Locking Device
 Bottom Entry



507F
3/4/5-Way Sanitary Ball Valve
 Full Port
 SS316 / SS316L
 Clamp, Tube Butt Weld and
 Extended Tube Butt Weld
 Mounting Pad
 Size: 1/2" to 4"
 Pressure: 1000 PSI CWP
 Temp: -20°F to 450°F
 Options: Locking Device
 Bottom Entry



509F
3/4/5-Way Flanged Ball Valve
 Full Port
 SS316 / WCB
 Flanged
 Mounting Pad
 Size: 1/2" to 6"
 Pressure: ANSI 150 / 300
 Temp: -20°F to 450°F
 Options: Locking Device
 Bottom Entry

SANITARY BUTTERFLY VALVE



707
Sanitary Butterfly Valve
 SS304
 Clamp, Tube Butt Weld
 Size: 1" to 4"
 Pressure: 145 PSI
 Temp: -60°F to 400°F
 Options: SS316 / SS316L
 Multi-Position Handle
 Pneumatic Actuation

OTHER STANDARD PRODUCTS



904
Y-Strainer
 SS316
 Threaded
 Size: 3/8" to 2"
 Pressure: 600 to 800 PSI CWP
 Temp: -20°F to 390°F



905 / 907
Gate Valve / Globe Valve
 SS316
 Threaded
 Size: 1/2" to 2"
 Pressure: 200 PSI CWP
 Temp: -20°F to 390°F



906
Swing Check Valve
 SS316
 Threaded
 Size: 1/2" to 2"
 Pressure: 200 PSI CWP
 Temp: -20°F to 390°F



908
Needle Valve
 SS316 / CS
 Threaded
 Size: 1/4" to 1"
 Pressure: 6000 PSI CWP
 Temp: -20°F to 390°F



B610 - B620
**Wafer / Lug Type
 Butterfly Valve**
 Body: Cast Iron
 Disc: SS316
 Seat: EPDM
 Size: 2" to 24"
 Pressure: 150 PSI CWP
 Temp: -4°F to 248°F (EPDM)
 14°F to 176°F (NBR)

DIRECT MOUNT



MULTI-PORT



SANITARY



INLINE INDUSTRIES, INC.

4701-A Littlejohn Street
Baldwin Park, CA 91706
Tel: (626) 813-6188
Fax: (626) 813-6186

Distributed by: